

- ❑ No Programming | Quick Installation
- ❑ Lifetime Warranty*
- ❑ Industry's Highest Accuracy: $\pm 0.5\%$



ETFE Tefzel® Paddle Rotor Design

- ❑ Patent Pending ShearPro® Contoured Paddle
- ❑ Reduced Turbulence = Reduced Wear = Longer Life
- ❑ Outstanding Flex Fatigue & Creep Resistance
- ❑ Surpassed only by Teflon® in Chemical Resistance
- ❑ Excellent Mechanical & Impact Properties
- ❑ Superior Wear Resistance vs PVDF

The TK Series Digital Flow Meters are easy to install with exceptional guaranteed long-life performance. TK Series Paddle Wheel Flow Sensors are highly repeatable, extremely rugged sensors that offer outstanding value and require no scheduled maintenance.

The TK Series has a process-ready output signal with a wide dynamic flow range of 0.3 to 33 ft/s | 0.1 to 10 m/s. The sensor measures liquid flow rates in full pipes.

The Truflo® TK Series sensors are offered in various materials and are available from 1/2" - 4" pipe sizes. The many material choices, including PVC, PP and PVDF make this model highly adaptable and chemically resistant to many corrosive liquid process applications.

The TK Series flow meter bodies are true-union designed up to 4" just as any true-union ball valve is designed. All models come completely pre-programmed with a bright LED Display that rotates 360°.

The Truflo® TK Series also comes equipped with a lifetime warranty on the paddle wheel assembly.




Features

- ❑ Display Rotates 360°
- ❑ 1/2" - 4" Size Range
- ❑ Bright LED Display | Visible in the Dark
- ❑ No K-Factor Programming Required
- ❑ No Pressure Drop
- ❑ Password Protected Security
- ❑ 4-20mA Output

New ShearPro® Design

- ❑ Superhydrophobic Design
- ❑ Contoured Flow Profile
- ❑ Reduced Turbulence
- ❑ Reduced Friction
- ❑ 78% Less Drag than Old Flat Paddle Design*



*Ref: NASA "Shape Effects on Drag" **


Zirconium Ceramic Rotor | Bushings

- ❑ Industry's Highest Impact and Chemical Resistant Properties
- ❑ Up to 15x the Wear Resistance vs. Regular Ceramic
- ❑ Nano-Polished Mirror Finished = Less Friction - Longer Life
- ❑ Integral Rotor Bushings, Reduce Wear & Fatigue Stress



Through-Pin Design

- ❑ Eliminates Finger Spread
- ❑ No Lost Paddles
- ❑ Increased Temp. Rating
- ❑ 360° Housing Protects Rotor



Technical Specifications

| General | | | | |
|---|---|------------------------|-----------------|-----------------|
| Operating Range | 0.3 to 33 ft/s | 0.1 to 10 m/s | | |
| Pipe Size Range | ½ to 4" | DN15 to DN100 | | |
| Linearity | ±0.5% of F.S @ 25°C 77°F | | | |
| Repeatability | ±0.5% of F.S @ 25°C 77°F | | | |
| Wetted Materials | | | | |
| Sensor Body | PVC (Dark) PP (Pigmented) PVDF (Natural) | | | |
| O-Rings | FKM EPDM* FFKM* | | | |
| Rotor Pin Bushings | Zirconium Ceramic ZrO ₂ | | | |
| Paddle Rotor | ETFE Tefzel® | | | |
| Electrical | | | | |
| Frequency | 49 Hz per m/s nominal | 15 Hz per ft/s nominal | | |
| Supply Voltage | 5 to 24 VDC ±10% regulated | 3 VDC | | |
| Supply Current | <1.5 mA @ 3.3 to 6 VDC | <20 mA @ 6 to 24 VDC | | |
| Max. Temperature/Pressure Rating - Standard and Integral Sensor Non-Shock | | | | |
| PVC | 180 psi @ 68°F | 40 psi @ 140°F | 12.5 bar @ 20°C | 2.7 bar @ 60°C |
| PP | 180 psi @ 68°F | 40 psi @ 190°F | 12.5 bar @ 20°C | 2.7 bar @ 88°C |
| PVDF | 200 psi @ 68°F | 40 psi @ 240°F | 14 bar @ 20°C | 2.7 bar @ 115°C |
| Operating Temperature | | | | |
| PVC | 32°F to 140°F | 0°C to 60°C | | |
| PP | -4°F to 190°F | -20°C to 88°C | | |
| PVDF | -40°F to 240°F | -40°C to 115°C | | |
| Outputs | | | | |
| TKM Series | 4-20mA + Frequency Pulse - Flow Frequency Pulse - Total | | | |
| Standards and Approvals | | | | |
| CE FCC RoHS Compliant | | | | |

See Temperature and Pressure Graphs for more information

Optional*

Temperature | Pressure Graphs | Non-Shock

Note: The Pressure/Temperature graphs are specifically for the Truflo® Flow Sensors. During system design the specifications of all components must be considered.

Model Selection

TKM - [] - [] - [] - []

| Material | Pipe Size | End Connections | Seals |
|-----------|---------------------|-----------------------|--------------------|
| P - PVC | 15 - ½" 50 - 2" | S - Sch 80 Soc | FKM Std |
| PP - PP | 20 - ¾" 80 - 3" | T - NPT | E - EPDM |
| PF - PVDF | 25 - 1" 100 - 4" | F - ANSI 150lb Flange | K - FFKM Kalrez® |
| | 40 - 1 ½" | B - Butt Fusion | |

■ = PVC ■ = PP ■ = PVDF

